

TRENNJAEGER SAWS KD 402 S

HIGHLIGHTS

- Versatile cutting possibilities
- Precision: The automatic movement and alignment provide exact cuttings
- Easy handling



TECHNICAL DATA AT A GLANCE

Machine type	U/min.	m/min	kW	kg
KD 402 S	3.000	min. 4.000 max. 7.000	2,2	

Further information on the machine series and numerous accessories can be found on our website:

www.wagner-maschinen.de/en/trennjaeger-saws/trennjaeger-milling-machines



DOUBLE-HEAD SAWS KD KD 402 S



ALL HIGHLIGHTS AT A GLANCE

- Automatic saw cut with electronic control unit, also with data transfer for different bevels
- Inclinations with an accuracy up to 300 intermediate positions per degree
- Saw blade diameter from 400 mm to 600 mm for versatile material dimensions
- Available for a material cutting length of 4,000 mm or 7,000 mm

Further information on the machine series and numerous accessories can be found on our website:

www.wagner-maschinen.de/en/trennjaeger-saws/trennjaeger-milling-machines

TECHNICAL DATA

- Dual ALU head with manual movement of the right head
- Manual alignment of the saw heads
- For straight and bevel cuts at 45° (right and left) and intermediate angles.
- For maximum from 3,455 mm
- Designed for the use of 2 hard metal saw blades Ø 400 mm
- TRI 400 V brake motor
- Power 2.2 kW
- Cutting speed 3,000 rpm
- Manual alignment of the saw heads
- Oleo-pneumatic blade feed
- Spraying device for lubricating the sawing bla


STANDARD EQUIPMENT

- 3 horizontal pneumatic vices that enable the tightening from the front
- 2 vertical pneumatic vices that enable the tightening from above
- 2-hand control console
- Manual movement of the moving head on 2 ball cage slides
- Cutting length reader on digital display
- Drive handwheel with Visu for fine adjustment of the position
- Blowing gun for the air cleaning
- Machining bench equipped with a millimetrecontrol ruler
- Mini cutting: 530 mm

DETAIL PICTURES







Mobile saw head

Swivelling table

Bevels on both sides