

CONVENTIONAL DRILLING MACHINES Series WSB

HIGHLIGHTS

- Solid construction
- able rotatable and swivelling
- Infinitely variable speed in 2 ranges



TECHNICAL DATA AT A GLANCE

Machine type	mm	→ min-¹	kg	kW kW
WSB 40R	40	65-540/245-2.000	385	1,5
WSB 50R	50	50-250/251-2.000	800	3,7

The WSB 40 is an ideal pillar drilling machine for workshops and industrial production. The equipment is a standard for multifunctional use.

Further information on the machine series and numerous accessories can be found on our website:

https://www.wagner-maschinen.de/en/drilling



PILLAR AND RADIAL DRILLING MACHINES WSB 40R/WSB 50R Digital

WSB 40 R with MK 4 holder – Order no..: **620604** WSB 50 R DIGITAL with MK 5 holder – Order no.: **620603**



ALL HIGHLIGHTS AT A GLANCE

- 3 automatic feeds
- Switch for autom. inversion to thread cutting
- Strong column 115 mm in diameter
- Rectangular table with 2 T-slots 16mm
- Table height adjustment via toothed rack
- Machined base plate with 2 T-slots
- Solid quill 75 mm in diameter with great rigidity

Additional highlights for WSB 50 R Digital:

- Digital readout with cycles
- Automatic drilling cycles with speed specification
- Thread-cutting cycles with pitch-calculation

Further information on the machine series and numerous accessories can be found on our website:

TECHNICAL DATA

- Drilling capacity in steel I 40/50 mm
- Tapping capacity in steel 19 mm
- Column diameter 115-180 mm
- Throat 265/360 mm
- Spindle diameter 75 mm
- Quill stroke 150 mm
- Spindle mount MK 4/MK 50
- Number of tools 3
- Feed size 0,2/0,1/0,05 mm/rev / infinitely

- Motor 1,5/3,7 kW
- Rectangular table dimensions $470 \times 560 / 470 \times 550$ mm
- Number and width of T-slots 2/16 / 2/18 mm
- Base plate dimensions 485x685 / 450x400 mm
- Machine height 2.000/2.600 mm
- Weight approx. 385/800 kg

STANDARD EQUIPMENT

- Infinitely variable speed range
- 3 automatic feeds
- Switch for automatic reversal for tapping
- Motor with two speeds
- Strong column
- Rectangular table with 2 T-slots
- Table height adjustment via toothed rack

- Machined base plate with 2 T-slots
- Ergonomic operating lever
- Belt guard
- Solid quill with great rigidity
- Complete electrical equipment 400 V / 50 Hz
- Operating tool and operating instructions
- CE-standard

DETAIL PICTURES











Further information on the machine series and numerous accessories can be found on our website: https://www.wagner-maschinen.de/en/drilling