

SWIVELLING FRAME BAND SAWS







Series TEBA

HIGHLIGHTS

- Robust and solid version
- Cast saw frame
- Cast machine table
- Cast material vice
- Central front operation



TECHNICAL DATA AT A GLANCE

Machine type	 mm	 m/min.	 90°	 -45°	 45°	 30°
TEBA 235 DG	2.710x27x0,9	40/80	235/ 230x230/ 280x180	160/ 165x165/ 185x80	185/ 185x185/ 185x100	115/ 80x80/ 115x80
TEBA 260 DG	2.880x27x0,9	40/80	260/ 240x240/ 300x200	180/ 160x160/ 190x100	200/ 190x190/ 190x100	125/ 120x120/ 120x130
TEBA 260 DG HA	2.880x27x0,9	15/90	260/ 240x240/ 300x200	180/ 160x160/ 190x100	200/ 190x190/ 190x100	125/ 120x120/ 120x130

Further information on the machine series and numerous accessories can be found on our website:
www.wagner-maschinen.de/en/trennjaeger-saws/band-saws

**SWIVELLING FRAME BAND SAWS –
MANUAL / SEMIAUTOMATIC
TEBA 235 DG/260 DG/260 DGHA**



ALL HIGHLIGHTS AT A GLANCE

- Robust and solid version
- Cast saw frame
- Cast machine table
- Cast turning plate
- Cast material vice with quick adjustment
- Motor with flanged gears
- Machine table also swivels with the bevel, so that no sawing is necessary
- Saw band guides with guide rollers and hard metal plates
- Feed cylinder with magnetic valve
- Infinitely adjustable feed control
- Scale on the turning plate

Further information on the machine series and numerous accessories can be found on our website:
www.wagner-maschinen.de/en/trennjaeger-saws/band-saws

TECHNICAL DATA TEBA 235 / 260 DG / 260 DGHA

- Dimensions (LxBxH)
1.950 x 1.650 x 1.000 /
1.650 x 950 x 1.450 / 1.850 x 1.550 x 2.050 mm
- Motor power 1,5 / 1,5 / 2,3 kW
- Weight 300 / 485 / 550 kg

STANDARD EQUIPMENT TEBA 235 / 260 DG / 260 DGHA

- Complete electrical equipment 400 V / 50 Hz
- Base frame with coolant system (TEBA 260 DG and TEBA 260 DGHA)
- Operational instructions / documentation
- CE standard

SPECIAL EQUIPMENT TEBA 235

- Saw frame hydraulically lowerable
- Chip brush over the impeller
- Halogen lamp LA 50
- Cutting line light
- 5 l coolant concentrate
- 5 l disposable container for micro-spray

SPECIAL EQUIPMENT TEBA 260 DG / 260 DGHA

- Chip brush driven
- Hydraulic lifting and lowering
- Support stand MR 280
- Cuttings chute
- 5 l coolant concentrate
- Minimum greasing system
- 5 l disposable container for micro-spray
- Halogen lamp LA 50
- Vertical clamping system, manually up to max. +/- 45°
- Vertical clamping system, hydraulically up to max. +/- 45°
- Band tensioning with pressure gauge
- Cutting line light

DETAIL PICTURES



Vertical tensioner, option



Pressure gauge, option



Lamp, option

Further information on the machine series and numerous accessories can be found on our website:
www.wagner-maschinen.de/en/trennjaeger-saws/band-saws

We reserve the right to make design changes in the course of technical improvements. Illustrations, dimensions and weights are not bin